



PIPE SIZE A	B	C	D	E	F	MATERIAL ³ THICKNESS	MATERIAL ³	FINISH ¹	# FASTENERS	Wt. (Lbs)	ORDERING PART NUMBER ²
2.375	6.00	6.00	6.00	.46	.388	.090 (13 GA)	STEEL	NO FINISH	8	3.41	2010-00110018-001
2.375	6.00	6.00	6.00	.46	.388	.090 (13 GA)	STEEL	GALVANIZED	8	3.41	2010-00110018-002
2.875	7.25	7.25	7.25	.53	.388	.105 (12 GA)	STEEL	NO FINISH	8	5.34	2010-00210018-001
2.875	7.25	7.25	7.25	.53	.388	.105 (12 GA)	STEEL	GALVANIZED	8	5.34	2010-00210018-002

1. FINISH:

Available in HDG (hot dipped galvanized) and available with no finish. Galvanized finish per ASTM A153 and ASTM A123.

2. PART NUMBER; 2010-00110018-001:

2010 signifies assembly of connector/s and corresponding hardware (bolts, washers and nuts).

-001 signifies nominal 2" pipe diameter (OD 2.375"), -002 signifies nominal 2 1/2" pipe diameter (OD 2.875")

10018 signifies a unique part number, 5 WAY CROSS.

-001 signifies the part finish, PLAIN, NO FINISH, -002 signifies the part finish, HDG (hot dipped galvanized).

3. ORDERING: The ordering part number consists of 4 quarters (1010-00010010-000) and 8 Grade 5 bolts, washers and nuts.

4. MATERIAL:

1008 CR Steel.

5. INSTALLATION:

For proper installation use 8 - 3/8 x 1 1/4 - 16 UNC minimum SAE Grade 5 steel bolts, washers and nuts or equivalent. Bolts can be either carriage or hex head type. Torque bolts evenly to 25 ft.-lbs. Avoid over tightening and use the supplied bolts, nuts and washers or equivalent.

6. DIMENSIONS: All dimensions are in inches.